

I/WE CLAIM:

1. A device for writing utensils comprising:
 a first engagement member including an exterior wall and an interior wall
 defining a channel that receives a first writing utensil along a first axis; and
 a second engagement member including an exterior wall and an interior wall
 defining a channel that receives a second writing utensil along a second access;
 wherein a portion of the first engagement member is tangentially connected to
 the second engagement member such that the first axis is offset at a selected angle
 from the second axis.

2. The device of claim 1, wherein the diameter of the first engagement member
 channel is different from the diameter of the second engagement member channel.

3. The device of claim 1, wherein at least one boss extends from at least a portion
 of the first member interior wall.

4. The device of claim 3, wherein at least one boss extends from at least a portion
 of the second member interior wall.

5. The device of claim 1 further including a first writing utensil positioned within
 the first engagement member and a second writing utensil positioned within the second
 engagement member.

6. The device of claim 5, wherein the first writing utensil differs from the second
 writing utensil.

7. The device of claim 6, wherein the first writing utensil is a pen and the second
 writing utensil is a pencil.

8. The device of claim 1, wherein the selected angle is about 45°.

9. A method of writing using the device of claim 1 including:
 (a) inserting a first writing utensil into the first engagement member;
 (b) inserting a second writing utensil into the second engagement member;

5

(c) selecting one of the first and second writing utensils as an active utensil;
and
(d) writing with the active utensil.

10. The method of claim 9, wherein (c) further includes:
positioning the device within a hand such that the second engagement member
becomes a bridge on which the active utensil rests.